

Part No:

24P-29P-MM-RA



2.4mm Male to 2.92mm Male Right Angle Adapter With Passivated Stainless Steel Body

The HASCO **24P-29P-MM-RA** is a Right Angle RF Adapter that operates from DC to 40 GHz. Our 2.4mm to 2.92mm Right Angle adapter has a male gender on both ends. The 24P-29P-MM-RA Adapter offers 1.33:1 max VSWR.

HASCO stocks an extensive selection of RF and Microwave between-series, in-series, right angle and low PIM adapters.

Electrical

- Frequency Range DC - 40 GHz
- VSWR DC - 40 GHz..... 1.3
- Impedance 50 Ohms
- Insertion Loss .05 √ Frequency
- Durability 500 Cycles Min

Environmental Data

- Temperature Range -55°C - +100°C

Material

- Dielectric Oxide-Noryl™, MIL-P-46129
- Center Conductor Beryllium Copper per ASTM-B-196, QQ-C-530
- Body SST, corrosion-resistant, Non-Magnetic 303, per ASTM A484 & A582
- Finish Center Contacts and solder components shall be plated per MIL-G-45204 Type II, Class I over Nickel plate per QQ-N-290. Body & Body components shall be passivated per ASTM A380

To view online, go to: <http://www.hasco-inc.com/adapters/adapters-between-series/2-4mm-male-to-2-92mm-male-right-angle-adapter/>