HA3A2-01 | DC - 3 GHz • 2 Watts | Outline Drawing

× V.	dB lue PART NO.	ATTENUATION
	1 HA3A2-01	± 0.4
	2 HA3A2-02	± 0.4
LASER MARKING	3 HA3A2-03	± 0.5
XX (ATTEN. dB)	4 HA3A2-04	± 0.5
MIL-STD-348A SMA MALE XXXX (YYWW) <u>MIL-STD-348A</u> SMA FEMALE	5 HA3A2-05	± 0.5
	6 HA3A2-06	± 0.5
	7 HA3A2-07	± 0.5
	8 HA3A2-08	± 0.5
	9 HA3A2-09	± 0.5
	0 HA3A2-10	± 0.6
8.4 5.0 6.6 SW 8.0	5 HA3A2-15	± 0.7
	10 HA3A2-20	± 0.7
	0 HA3A2-30	± 0.8
LTR DESCRIPTION DATE APPR. DRAWN BY: ABC CHECKED BY: ABC 5214 Box	sai Street • Moor	Dark CA 02021
- RELEASE 12/16 TAC APPROVED BY: ABC (888) 498	-3242 • sales@ha	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF	<u>co-inc.com</u>	
HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANU- FACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRIT- TEN PERMISSION OF HASCO COMPONENTS.	N/A	А
Image: Constraint of the second se	REV:	
ALL DIMS IN MILLIMETERS 1 PLACE ±0.20 ANGLE ±1.0° 2 PLACE ±0.10 FINISHES: SEE DATA SHEET HA3A2-0		-
THIS DRAWING IS A CONTROLLED DOCUMENT		

To view online, go to: 1 dB - Fixed Attenuator SMA Male To SMA Female Up To 3 GHz Rated To 2 Watts With Gold Plated Brass Body