								**dB Value	PART NO.	ATTENUATION
								1	HA3A2-01	± 0.4
								2	HA3A2-02	± 0.4
	LASER MARKING XX (ATTEN. dB)							3	HA3A2-03	± 0.5
								4	HA3A2-04	± 0.5
_	<u>MIL-STD-348A</u> SMA MALE			XXXXX (M	XXXX (YYWW)	<u>MIL-STD-348A</u> SMA FEMALE		5	HA3A2-05	± 0.5
								6	HA3A2-06	± 0.5
							7	HA3A2-07	± 0.5	
HA3A2-XX								8	HA3A2-08	± 0.5
	HEX		XXX			8		9	HA3A2-09	± 0.5
	ļĻ			Э⊣				10	HA3A2-10	± 0.6
		8.	4	5.0 6.6		SW 8.0	15	HA3A2-15	± 0.7	
Ref 26.6							20	HA3A2-20	± 0.7	
	-							30	HA3A2-30	± 0.8
LTR	DESCRIPTION	DATE	APPR.	DRAWN BY: ABC	снескед ву: АВС			214 Ropcai Si	troot - Moorr	ork CA 02021
-	RELEASE	12/16	TAC	APPROVED BY: ABC THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED		HASCO, INC		5214 Bonsai Street • Moorpark, CA 93021 (888) 498-3242 • sales@hasco-inc.com		
						COMPON	www.hasco-in	w.hasco-inc.com		
_				NOR USED - IN WHOLE OR IN P FACTURE OR SALE OF OTHER IT	OR USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANU- ACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRIT- EN PERMISSION OF HASCO COMPONENTS.		CAGE CODE: 0T8L4	SCALE: N/A	SIZE:	А
				TOLERANCES - UNLESS OTHERW	VISE NOTED:	FINISHES:	PART NO,/DRAWING NO.		REV:	
			ALL DIMS IN MILLIMETERS 1 PLACE ± 0.20 ANGLE $\pm 1.0^{\circ}$ 2 PLACE ± 0.10		SEE DATA SHEET	HA3A2-06				
Т	HIS DRAWING IS A CONTRO	LLED DOCL	IMENT							

To view online, go to: 6 dB - Fixed Attenuator SMA Male To SMA Female Up To 3 GHz Rated To 2 Watts With Gold Plated Brass Body