								**dB Value	PART NO.	ATTENUATION	
								1	HA3A2-01	± 0.4	
				LASER MARKIN XX (ATTEN. de		<u>MIL-STD-348A</u> SMA FEMALE		2	HA3A2-02	± 0.4	
					EN. dB)			3	HA3A2-03	± 0.5	
								4	HA3A2-04	± 0.5	
N	<u>/IL-STD-348/</u> SMA MALE	<u>+</u>		XXXX (Y				5	HA3A2-05	± 0.5	
			/	$\langle + + + + + + + - + + - + + - + + + + - + + + + + + + +$			6	HA3A2-06	± 0.5		
	0	\succ		∢∏ _		ו ו		7	HA3A2-07	± 0.5	
	8.0		3A2-XX	< <u> </u>		0.6%		8	HA3A2-08	± 0.5	
	HEX		XXX			8		9	HA3A2-09	± 0.5	
				<u>н</u>				10	HA3A2-10	± 0.6	
		8.	4		5.0 6.6		SW 8.0	15	HA3A2-15	± 0.7	
	-		·		F		20	HA3A2-20	± 0.7		
						-1		30	HA3A2-30	± 0.8	
_TR	DESCRIPTION	DATE	APPR.	DRAWN BY: ABC	снескед ву: АВС			5214 Bonsai S	rreet • Moorn	ark CA 93021	
-	RELEASE	12/16	TAC	APPROVED BY: ABC		$ \square HASCO, INC (88)$		(888) 498-324	14 Bonsai Street • Moorpark, CA 93021 88) 498-3242 • sales@hasco-inc.com		
				IESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED		COMPONENTS DISTRIBUTOR WWW.hasco-inc.co					
				NOR USED - IN WHOLE OR IN F FACTURE OR SALE OF OTHER	R USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANU- TURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRIT- I PERMISSION OF HASCO COMPONENTS.		CAGE CODE: 0T8L4	scale: N/A	SIZE:	А	
				TOLERANCES - UNLESS OTHER	WISE NOTED:		PART NO./DRAWING NO.		REV:		
			ALL DIMS IN MILLIMETERS 1 PLACE ±0.20 ANGLE ±1.0° 2 PLACE ±0.10		FINISHES: SEE DATA SHEET	HA3A2-09			-		
		DLLED DOCL		1							