								**dB Value	PART NO.	ATTENUATION
								value 1	HA3A2-01	± 0.4
								2	HA3A2-02	± 0.4
								3	HA3A2-03	± 0.5
LASER MARKING XX (ATTEN. dB)								4	HA3A2-04	± 0.5
<u> </u>	<u>MIL-STD-348A</u> SMA MALE	` -		XXXX (Y1	′WW)	MIL-STD-348A SMA FEMALE		5	HA3A2-05	± 0.5
			/	< г				6	HA3A2-06	± 0.5
					ז 📃 ו		7	HA3A2-07	± 0.5	
HA3A2-XX								8	HA3A2-08	± 0.5
	HEX		XXX			ð V		9	HA3A2-09	± 0.5
	ļĻ			Э				10	HA3A2-10	± 0.6
			4	5.0 6.6		SW 8.0	15	HA3A2-15	± 0.7	
	Ref_26.6					-		20	HA3A2-20	± 0.7
	1-							30	HA3A2-30	± 0.8
LTR	DESCRIPTION	DATE	APPR.	DRAWN BY: ABC	CHECKED BY: ABC				rreet • Moorn	ark, CA 93021
-	RELEASE	12/16	TAC	APPROVED BY: ABC THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANU- FACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRIT- TEN PERMISSION OF HASCO COMPONENTS.			CO, INC (888) 498-3242	2 • sales@has	co-inc.com
							vww.hasco-in	w.hasco-inc.com		
						MATERIALS: SEE DATA SHEET	CAGE CODE: 0T8L4	scale: N/A	SIZE:	А
				OLERANCES - UNLESS OTHERWISE NOTED:		FINISHES:	PART NO./DRAWING NO.		REV:	
			ALL DIMS IN MILLIMETERS 1 PLACE ± 0.20 ANGLE $\pm 1.0^{\circ}$ 2 PLACE ± 0.10		SEE DATA SHEET	HA3A2-10				
Т	HIS DRAWING IS A CONTRO)LLED DOCU	IMENT							

To view online, go to: 10 dB - Fixed Attenuator SMA Male To SMA Female Up To 3 GHz Rated To 2 Watts With Gold Plated Brass Body