HLL283R-S1-S2-24



Part No:

The HASCO **HLL283R Series Cable** is a low loss LL283 cable that operates from DC to 26.5 GHz. This cable series is constructed with SMA Male to SMA Female connectors. These cables are internally ruggedized with multi-layer copper spiral and braided armor. They offer excellent phase and amplitude stability vs. flexure. The HLL283R Series cables offer 1.30:1 max VSWR.

The HLL283R-S1-S2-24 is RoHS Compliant.



HASCO offers many types and configurations of RF and microwave cable assemblies and can support most requirements, such as flexible, conformable, semi-rigid, VGA, low-loss, phase stable, armored, jacketed and more; all assembled with the highest quality RF connectors.



SMA Male to SMA FemaleTest Cable using LL283 Low Loss Ruggedized Flexible Cable, Excellent Phase and Amplitude Stability vs. Flexure, DC- 26.5 GHz, 24 Inches

Specifications

Frequency Range	DC - 26.5 GHz	
Insulation Resistance	5,000ΜΩ	
Insertion Loss	≤1.9dB @ 26.5 GHz	
• VSWR	1.30:1 MAX	
Impedence	50 Ohms	
Dielectric Withstanding Voltage	1,000V Max at Sea Level	
Min. Bend Radius	1.8" (dynamic)7" (static)	
Velocity of Propagation	76%	
• RF Leakage	>90 dB	
Phase Stability	≤±0.03dB @ 26.5 GHz	
Phase Stability over Flexure	≤±2.7° @ 26.5 GHz	
Dielectric Withstanding Voltage	1,000V Max at Sea Level	
Capacitance	27pf/ft=88pf/m	
Temperature Range	-55°C - +125°C	

Materials and Finishes

DESCRIPTION	MATERIALS	FINISH OR COLOR
Connectors	Stainless Steel	Passivated
 Insulation 	PTFE	N/A
Inner and Outer Shield	Copper	Silver Plated
Inner Armor	Copper	Silver Plated
• Jacket	FEP	N/A
Outer Armor	PTFE Braid	Purple

