


THIS DRAWING UNPUBLISHED.

RELEASED FOR PUBLICATION

LOC		DIST		REVISIONS			DATE	DWN	APVD
P	LTR								
-	-	-	-	-	-	-	-	-	



NOTES:

1.ELECTRICAL:

- 1.1 IMPEDANCE: 50Ω
- 1.2 INSULATION RESISTANCE:5000MΩ MIN
- 1.3 FREQUENCY RANGE: DC~40GHz
- 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
- 1.5 VSWR≤1.35:1@DC-40GHz
- 1.6 INSERTION LOSS: ≤3.2dB@40GHz

2.ENVIRONMENTAL:

TEMPERATURE RANGE: -55° to +85°

3. CONNECTOR MATERIAL AND FINISH:

BODY: STAINLESS STEEL TYPE 303, PASSIVATE
 NUT: STAINLESS STEEL TYPE 303, PASSIVATE
 CENTER CONTACT: BERYLLIUM COPPER
 , GOLD PLATING
 DIELECTRIC: PEEK, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	DWP	15/08/2012	HASCO		
		CHK			HyTech Associates Sales Company, Inc		
DIMENSIONS INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME HLL150A Series		
		0 PLC	±0.25	PRODUCT SPEC	40GHz Ultra Low Loss Flexible Cable Assemblies		
		1 PLC	±0.15	APPLICATION SPEC	Excellent Phase Stability		
		2 PLC	±0.12		vs. Flexure & Temperature		
		3 PLC	±	SIZE	CAGE CODE	DRAWING NO	
		4 PLC	±	A3	OT8L4	HLL150A-29P-29P-36	
MATERIAL SEE TABLE		FINISH SEE TABLE		WEIGHT			
				CUSTOMER DRAWING		SCALE	4: 1
						SHEET	1 OF 1
						RVE	1