


NOTES:

1. ELECTRICAL:
- 1.1 IMPEDANCE: 50Ω
 - 1.2 INSULATION RESISTANCE: 5000MΩ MIN
 - 1.3 FREQUENCY RANGE: DC~26.5GHz
 - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - 1.5 VSWR ≤ 1.25:1 @ DC~26.5GHz
 - 1.6 INSERTION LOSS: ≤ 2.1dB @ 26.5GHz

2. ENVIRONMENTAL:
- TEMPERATURE RANGE: -40° to +85°

3. CONNECTOR MATERIAL AND FINISH:
- BODY: STAINLESS STEEL TYPE 303, PASSIVATE
 - NUT: STAINLESS STEEL TYPE 303, PASSIVATE
 - CENTER CONTACT: BERYLLIUM COPPER
 - , GOLD PLATING
 - DIELECTRIC: PEEK, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	HASCO HyTech Associates Sales Company, Inc			
		CHR				
DIMENSIONS INCHES 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±— 4 PLC ±— ANGLES ±1°		APVD NAME HVNA26® Series DC~26.5GHz Vector Network Analyzer Flexible & Phase Stable Test Cable Assemblies		
				PRODUCT SPEC APPLICATION SPEC		
MATERIAL SEE TABLE		FINISH SEE TABLE		SIZE A3 CAGE CODE OT8L4 DRAWING NO HVNA26-35NMD-35J-24		
				WEIGHT CUSTOMER DRAWING		
		SCALE 4: 1 SHEET 1 OF 1 RVE 1				