


**Notes:**

- Operating Frequency: 18 GHz
- Glass Meniscus .005 Max (2X)
- Glass Type: Corning 7070 or Equivalent
- Hermeticity  $1 \times 10^{-6}$  cc/sec @ 1 atm Helium
- Body Material: Kovar
- Gold Plate, ASTM B488-01, Type III, Code A, Class 1.25 (50 $\mu$  In Min) Over Nickel, 100 $\mu$  In Min
- Operating Temperature: -55°C to +300°C

|                               |                                   |  |  |
|-------------------------------|-----------------------------------|--|--|
| Part Number: <b>HA-079</b>    | Rev: <b>B</b>                     | Unless otherwise Specified, Dimensions Are In Inches<br><br>Tolerances Dimensions<br>.x +/-<br>.xx +/-<br>.xxx +/-<br>Fractions<br>+/- |  <b>HASCO, INC</b><br>COMPONENTS DISTRIBUTOR<br><br>5214 Bonsai St. • Moorpark, CA 93021<br>888-498-3242 • www.hasco-inc.com<br>sales@hasco-inc.com |
| Material: <b>Noted</b>        | Date: <b>01-23-12</b>             |  |  |
| Title: <b>50 Ohm Feedthru</b> | Cage Code: <b>0T8L4</b>           |  |  |
| Scale: <b>N/A</b>             | Last Rev. Change: <b>01-23-12</b> |  |  |
| Drawn By: <b>J. Shade</b>     | Checked by: <b>T. Cates</b>       |  |  |