

Glass: 7052
or Equivalent

Dia.:
 0.158 ± 0.015

Pin Dia.
 0.020 ± 0.005

Kovar

Pin A:
 0.095 ± 0.005


Body Length:
 0.060 ± 0.002

Pin B:
 0.500 ± 0.005

Square Cut

Notes:

- Operating Frequency: 8 GHz
- Glass Meniscus .005 Max (2X)
- Glass Type: Corning 7052 or Equivalent
- Hermeticity 1×10^{-8} cc/sec @ 1 atm Helium
- Body Material: Kovar
- Gold Plate, ASTM B488-01, Type III, Code A, Class 1.25 (50 μ In Min) Over Nickel, 100 μ In Min
- Operating Temperature: -55°C to +300°C

Part Number: HA-184	Rev: -	Unless otherwise Specified, Dimensions Are In Inches Tolerances Dimensions .x +/- .xx +/- .xxx +/- Fractions +/-	 5214 Bonsai St. • Moorpark, CA 93021 888-498-3242 • www.hasco-inc.com sales@hasco-inc.com
Material: Noted	Date: 12-12-98		
Title: 50 Ohm Feedthru	Cage Code: OT8L4		
Scale: N/A	Last Rev. Change:		
Drawn By: J. Shade	Checked by: T. Cates		