




**HASCO**  
COMPONENTS

888-498-3242  
[www.hasco-inc.com](http://www.hasco-inc.com)



Scan or Click to  
[View and Download](#)  
[HASCO Catalog Pages](#)

# DC BLOCKS

HASCO offers a selection of Inner-Only and Inner / Outer DC Blocks with 1.85mm, 2.4mm, 2.92mm, SMA, or Type N Male to Female connectors. Depending on the model, they operate down to 7 KHz and up to 65 GHz.

Several of the Inner-Only DC Blocks and the Inner/ Outer DC Blocks will handle maximum DC voltages up to 200 VDC. All of our DC Blocks are precision designs that are constructed using Passivated Stainless Steel bodies.

# DC BLOCKS

PHOTO	TYPE/PART #	FREQUENCY	INSERTION LOSS	TEMP RANGE	VSWR	POWER	MATERIALS
	<b>SMA INNER/OUTER HDC18IO</b>	10MHz-18 GHz	0.75dB	-65° - +125°C	1.35:1	5 WATT AVG. 200V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> High Temp. Plastic</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>SMA INNER ONLY HDC23I</b>	7KHz-23 GHz	0.75dB	-65° - +125°C	1.35:1	2 WATT AVG. 100V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> Passivated SS</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>N INNER/OUTER HDC18NIO</b>	10MHz-18 GHz	0.85dB	-65° - +125°C	1.35:1	20V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> High Temp. Plastic</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>N INNER ONLY HDC18NI</b>	10MHz-18 GHz	0.60dB	-65° - +125°C	1.35:1	100V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> Passivated SS</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>2.92mm INNER ONLY HDC40I</b>	10MHz-40 GHz	0.75dB	-65° - +125°C	1.45:1	200V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> Passivated SS</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>2.4mm INNER ONLY HDC50I</b>	10MHz-40 GHz	1.25dB	-35° - +85°C	1.65:1	100V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> Passivated SS</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>
	<b>1.85mm INNER ONLY HDC65I</b>	DC-65 GHz	1.25dB	-40° - +85°C	1.60:1	1 WATT 16V	<ul style="list-style-type: none"> <li>● <b>Housing:</b> Passivated SS</li> <li>● <b>Connector:</b> Passivated SS</li> <li>● <b>Contact:</b> Gold Plated BeCu</li> </ul>

