


NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.




HOUSING:	STEEL, CRES ALLOY UNS-S30300 PER ASTM-A582. PASSIVATE PER QQ-P-35.
CONTACT:	BeCu UNS-C17300 PER ASTM-B-196/197 GOLD PLATE PER MIL-G-45204
DIELECTRIC INSULATOR:	VIRGIN TFE FLUOROCARBON PER ASTM-D-1710 AND ASTM-D-1457
BEAD RING:	ULTEM 1000 PER ASTM-D-5205
MATERIAL & FINISH	

3. DIMENSIONS IN PARENTHESIS (XXX) ARE MILLIMETERS.
2. INTERFACE IN ACCORDANCE WITH MIL-STD-348.
1. ALL DIMENSIONS ARE IN INCHES, 3. ALL ANGLES ARE IN DEGREES.

CONTACT GAGING SPEC.	91B52105
SPECIFICATIONS	91B52088
INTERFACE	91B56188
SPECIFICATION GROUP	DRAWING NO.

NOTES: UNLESS OTHERWISE SPECIFIED

REV B3	ECN: 7907	INIT: EJO	DATE: 3/30/05	APRVD. R.BOAK	DATE: 3/30/05	TITLE MODEL 212-512SF SMA JACK 4 HOLE 3/8 SQ FLANGE TO ACCEPT (.020) DIA. PIN	
 Southwest Microwave, Inc. 9055 South McKemy Street Tempe, Arizona 85284-2946 Telephone (480) 783-0201 Fax (480) 783-0360						DRN BY: DK DATE: 3/95 DWG. NO. SCALE: 3:1 SHEET: 1 OF 1	REV. B3 79B53992