


NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.



HOUSING:	STEEL, CRES ALLOY UNS-S30300 PER ASTM-A582. PASSIVATE PER QQ-P-35.
CONTACT:	BeCu UNS-C17300 PER ASTM-B-196/197 GOLD PLATE PER MIL-G-45204
DIELECTRIC INSULATOR:	VIRGIN TFE FLUOROCARBON PER ASTM-D-1710 AND ASTM-D-1457
BEAD RING:	ULTEM 1000 PER ASTM-D-5205
MATERIAL & FINISH	

3. DIMENSIONS IN BRACKETS [XXX] ARE MILLIMETERS.
2. INTERFACE IN ACCORDANCE WITH MIL-STD-348.
1. ALL DIMENSIONS ARE IN INCHES, 3. ALL ANGLES ARE IN DEGREES.

NOTES: UNLESS OTHERWISE SPECIFIED

CONTACT GAGING SPEC.	91B52107
SPECIFICATIONS	91B52087
INTERFACE	91B56188
SPECIFICATION GROUP	DRAWING NO.

REV A4	ECN: 7907	INIT: EJO	DATE: 4/29/05	APRVD. R.BOAK	DATE: 4/29/05
-----------	--------------	--------------	------------------	------------------	------------------



Southwest Microwave, Inc.
 9055 South McKemy Street
 Tempe, Arizona 85284-2946
 Telephone (480) 783-0201
 Fax (480) 783-0360

TITLE
 MODEL 214-511SF
 EXT PWR SMA JACK 2 HOLE .550L FLANGE
 TO ACCEPT (.015) DIA. PIN

DRN BY: DK	DATE: 12/95	DWG. NO.	REV. A4
SCALE: 3:1	79B54002		
SHEET: 1 OF 1			