

HOUSING: STEEL, CRES ALLOY UNS-S30300  
COUPLING NUT: PER ASTM-A582.  
PASSIVATE PER QQ-P-35.

CONTACT: BeCu  
UNS-C17300 PER ASTM-B-196/197.  
GOLD PLATE PER MIL-G-45204.

DIELECTRIC: VIRGIN TFE FLUOROCARBON PER  
ASTM-D-1710, TYPE 1, GRADE 1,  
CLASS B, AND ASTM-D-1457.

BEAD RING: ULTEM 1000 PER MIL-P-46184.

RETAINING RING: BeCu  
UNS-C17300 PER ASTM-B-196/197.


GASKET: SILICONE RUBBER PER MIL-R-5847  
& ZZ-R-765.

MATERIAL & FINISH

APPLICATION NOTE	91B52155
CONTACT SPECIFICATION	91B52103
SPECIFICATIONS	91B52090
INTERFACE	91B52002
SPECIFICATION GROUP	DRAWING NO.

NOTES:

1. SMA INTERFACE IN ACCORDANCE WITH MIL-STD-348.

DRAWN DK	DATE 12-19-95	APRVD. GH	DATE 1/4/96	TITLE 221-501SF, SMA PLUG, EXTENDED POWER, .650 LONG THREAD-IN TO ACCEPT .015 DIA PIN
 <p>Southwest Microwave, Inc. 9055 South McKemy Street Tempe, Arizona 85284-2946 Telephone (480) 783-0201 Fax (480) 783-0360</p>				<p>DATE 12/95</p> <p>DWG. NO. 79B54114</p> <p>REV. A1</p>
SHEET 1 OF 1				