



- HOUSING
& C-NUT: STEEL, CRES ALLOY UNS-S30300
PER ASTM-A582
PASSIVATE PER QQ-P-35
- CONTACT: BERYLLIUM COPPER ALLOY
UNS-C17300 PER ASTM-B-196/197
GOLD PLATE PER MIL-G-45204
- DIELECTRIC: VIRGIN TFE FLUOROCARBON PER
ASTM-D-1710, TYPE 1, GRADE 1,
CLASS B, & ASTM-D-1457
- BEAD RING: ULTEM 1000 PER ASTM-D-5205
- GASKET: SILICONE RUBBER PER ZZ-R-765
- RETAINING
RING: PHOSPHOR BRONZE PER QQ-B-746
- MATERIAL & FINISH

2. N-TYPE INTERFACE CONFORMS TO MIL-STD-348 &
MIL-C-39012.

1. ALL DIMENSIONS ARE IN INCHES, ALL ANGLES
ARE IN DEGREES.

NOTES: UNLESS OTHERWISE SPECIFIED

DRAWN RB	DATE 10-14-98	APRVD. DRB	DATE 10-16-98
-------------	------------------	---------------	------------------

TITLE	311-04SF N-TYPE PLUG, 4 HOLE, 1.00 SQ FLANGE ACCEPTS $\phi.020$ PIN
-------	---



Southwest Microwave, Inc.
9055 South McKemy Street
Tempe, Arizona 85284-2946
Telephone (480) 783-0201
Fax (480) 783-0360

SCALE	2/1
SHEET	1 OF 1

DWG. NO.	79C55508
----------	----------

REV.	A
------	---