HT65F





1 Watt RF Load Termination with 1.85 Female Connector DC - 65 GHz

The HASCO **HT65F** is an RF termination (also called RF load or dummy load) that operates from DC to 65 GHz and handles up to 1 Watt (CW). Our 1.85mm termination/load has a female gender. HT65F 1.85mm termination offers 1.45:1 max VSWR.

The **HT65F** is RoHS Compliant.



RF load/terminations are indispensable components in many RF, microwave and millimeter wave systems where signal reflection from unused ports can potentially damage the device or reduce the signal integrity. By using a termination on an unused port with a matched load (dummy load), the incident energy will be absorbed with minimal reflection. These termination components are commonly used to terminate devices such as couplers, circulators, and switches. They are also widely used in measurement systems to ensure accurate results. HASCO offers a huge selection of RF, microwave and millimeter wave terminations up to 65 GHz with excellent performance over the entire operating range and power handling capabilities up to 800 Watt (CW).

Electrical

• Frequency Range DC - 65 GHz

• VSWR DC - 18 GHz......1.20:1

18 - 40 GHz......1.30:1 40 - 65 GHz......1.45:1

• Impedence 50 Ohms

• Power 1 Watt Average @ 25°C

Derated Linearly to <10% @ 100°C

Environmental Data

• Temperature Range -55°C - +100°C

Material

Insulator/Dielectric Teflon

• Center Contact Beryllium Copper, Gold Plated IAW MIL-PRF-39012

Housing Passivated Stainless Steel, IAW ASTM-A484 & ASTM-A582,

Alloy 303, Cond. A

To view online, go to: https://www.hasco-inc.com/terminations/1-watt-rf-load-termination-with-1-85mm-female-connector-dc-65-ghz/

