


Part No:

HWLPT34-2-ES



*WR-34 Low Power Waveguide Termination, 2 W Average,
1 KW Max - 22 GHz to 33 GHz*

Electrical

- Frequency Range 22 - 33 GHz
- VSWR 1.25:1 Max
- Average Power 2 W
- Peak Power 1 KW
- Temperature Range -54°C to 85°C

Material

- Material Aluminum Alloy
- Finish Clear Chem Film


HWLPT34-2-ES is a general purpose WR-34 waveguide termination from HASCO. This waveguide termination will operate from 22 to 33 GHz. A Waveguide Termination is a passive RF device specifically designed to prevent RF signals from reflecting back from open-ended or unused waveguide ports. Waveguide Terminations dissipate RF energy by producing heat energy. HASCO offers a series of waveguide terminations covering the waveguide sizes WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34, WR-42, WR-51, WR-62, WR-75, WR-90 and WR-112.

The HWLPT34-2-ES is RoHS compliant.



HASCO stocks an extensive selection of RF and Microwave between-series, in-series, right angle and low PIM adapters.

WR-34 Low Power Waveguide Termination | 22 - 33 GHz | Outline Drawing



LTR	DESCRIPTION	DATE	APPR.	DRAWN BY: NS	
-	RELEASE	7/23	TC	REVIEWED BY: JS	APPROVED BY: TC
				THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANUFACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRITTEN PERMISSION OF HASCO COMPONENTS.	
THIS DRAWING IS A CONTROLLED DOCUMENT					



5214 Bonsai Street • Moorpark, CA 93021
(888) 498-3242 • sales@hasco-inc.com
www.hasco-inc.com

MATERIALS: SEE DATA SHEET	CAGE CODE: 0T8L4	SCALE: N/A	SIZE: A
FINISHES: SEE DATA SHEET	PART NO./DRAWING NO. HWLPT34-2-ES		REV: -