HWSS03-1.0-ER

Part No:



The HASCO WR-3 Millimeter Waveguide Straight Section **HWSS03-1.0-ER** operates from 220 GHz to 330 GHz. This WR-3, waveguide section is constructed with a Round UG-387/U-M Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



WR-3 Millimeter Waveguide Straight Section, 1 Inch 220 GHz to 330 GHz

| Electrical | |
|-------------------|---|
| Frequency Range | 220 to 330 GHz |
| Impedence | 50 Ohms |
| Insertion Loss | 2.5 dB Typical |
| Return Loss | 18 dB Typical |
| • Waveguide | WR-3 |
| • Flange | UG-387/U-M Precision Anti-Cocking Flange |
| • Length | 1 Inch |
| Temperature Range | 25°C (specification), -40°C to 85°C (operating) |
| | |
| Material | |
| • Body | Gold plated Brass |
| | |
| | |
| | |

