HWSS10-2.0-ER-1



Part No:

The HASCO WR-10 Millimeter Waveguide Straight Section HWSS10-2.0-ER-1 operates from 75 GHz to 110 GHz. This WR-10, W-Band waveguide section is constructed with a Round UG-387/U-M Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



WR-10 Millimeter Waveguide Straight Section, 2 Inch 75 GHz to 110 GHz, W-Band

Specifications					
Frequency Range	75 GHz to 110 GHz				
• VSWR	1.03:1				
• Length	2 inch				
• RF Ports	WR-10 Waveguide with UG-387/U-M Round Flange				
Temperature Range	220°C Max				
Material					
• Material	Brass				
• Finish	Gold Plated per MIL-DTL-45204				

	0.10	<u> </u>	050-						
						- 2"			
LTR	DESCRIPTION	DATE	APPR.	CREATED BY: NS	CHECKED BY: JMS			E 214 Doncoi Stroot A	
-	RELEASE	11/22	TAC	REVIEWED BY: GC	APPROVED BY: TAC		ASCO MPONENTS	5214 Bonsai Street • M (888) 498-3242 • sales	@hasco-inc.com
A	UPDATED PHOTO	01/26	TAC	THESE DRAWINGS AND	SPECIFICATIONS ARE THE	CO.	MPONENTS	www.hasco-inc.com	
	NOT BE REPROE WHOLE OR IN PA UFACTURE OR S	NOT BE REPRODUCED, WHOLE OR IN PART - AS UFACTURE OR SALE OF	O COMPONENTS AND SHALL ED, COPIED NOR USED - IN - AS THE BASIS FOR THE MAN- E OF OTHER ITEMS WITHOUT TEN PERMISSION OF HASCO	MATERIALS: SEE DATA SHEET	CAGE CODE: 0T8L4	SCALE: N/A	SIZE:		
TH	IS DRAWING IS A CONTRC	DLLED DOCL	JMENT	COMPONENTS.		FINISHES: SEE DATA SHEET	PART NO/DRAWING NO.	0-2.0-ER-1	REV:

Г