HWSS12-2.0-ER-1





The HASCO WR-12 Millimeter Waveguide Straight Section **HWSS12-2.0-ER-1** operates from 60 GHz to 90 GHz. This WR-12, E-Band waveguide section is constructed with a Round UG-387/U-M Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.

WR-12 Millimeter Waveguide Straight Section, 2 Inch 60 GHz to 90 GHz, E-Band

Specifications

• Frequency Range 60 GHz to 90 GHz

• VSWR 1.03:1

• Length 2 inch

• RF Ports WR-12 Waveguide with UG-387/U-M Round Flange


• Temperature Range 220°C Max

Material

Material Brass

• Finish Gold Plated per MIL-DTL-45204

WR-12 Millimeter Waveguide Straight Section 2 inch | 60 GHz to 90 GHz | Outline Drawing



Product specifications subject to change without notification.

© 2022 HASCO COMPONENTS