Part No:

HWSS28-1.0-ES



The HASCO WR-28 Millimeter Waveguide Straight Section **HWSS28-1.0-ES** operates from 26.5 GHz to 40 GHz. This WR-28, Ka-Band waveguide straight section is constructed with a Square UG-599/U Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



WR-28 Millimeter Waveguide Straight Section, 1 Inch 26.5 GHz to 40 GHz, Ka-Band

Specifications	
Frequency Range	26.5 GHz to 40 GHz
• VSWR	1.02:1
Impedence	50 Ohms
• Length	1 inch
• RF Ports	WR-28 Waveguide with UG-599/U Flange
E. L. L.	
Environmental D	
Temperature Range	220°C Max
Material	
• Waveguide	OFHC Copper
• Flange	Square UG-599/U, Brass
• Finish	Gold Plated per MIL-DTL-45204

HWSS28-1.0-ES | 26.5 GHz to 40 GHz | Outline Drawing

