Part No:

HWSS28-1.5-ES



The HASCO WR-28 Millimeter Waveguide Straight Section **HWSS28-1.5-ES** operates from 26.5 GHz to 40 GHz. This WR-28, Ka-Band waveguide straight section is constructed with a Square UG-599/U Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



WR-28 Millimeter Waveguide Straight Section, 1.5 Inch 26.5 GHz to 40 GHz, Ka-Band

| Specifications | |
|-------------------|--------------------------------------|
| Frequency Range | 26.5 GHz to 40 GHz |
| • VSWR | 1.02:1 |
| Impedence | 50 Ohms |
| • Length | 1.5 inch |
| RF Ports | WR-28 Waveguide with UG-599/U Flange |
| | |
| Environmental D | ata |
| Temperature Range | 220°C Max |
| Material | |
| • Waveguide | OFHC Copper |
| • Flange | Square UG-599/U, Brass |
| • Finish | Gold Plated per MIL-DTL-45204 |

