Part No:

## HWSS34-1.5-ES



The HASCO WR-34 Millimeter Waveguide Straight Section **HWSS34-1.5-ES** operates from 22 GHz to 33 GHz. This WR-34, waveguide straight section is constructed with a Square UG-595/U-M Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anti-cocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



## *WR-34 Millimeter Waveguide Straight Section, 1.5 Inch* 22 GHz to 33 GHz

Specifications	
Frequency Range	22 GHz to 33 GHz
• VSWR	1.02:1
Impedence	50 Ohms
• Length	1.5 inch
• RF Ports	WR-34 Waveguide with UG-595/U-M Flange
Environmental D	
Environmental Da	ata
Environmental Da	ata 220°C Max
• Temperature Range	
• Temperature Range Material	220°C Max

HWSS34-1.5-ES | 22 GHz to 33 GHz | Outline Drawing

