Part No:

HWTW03-1-ER



The HASCO WR-3 Millimeter Waveguide 90° Twist **HWTW03-1-ER** operates from 220 GHz to 325 GHz. This WR-3, waveguide 90° Twist is constructed with a Round UG-387/U-M Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anticocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.



WR-3 Millimeter Waveguide 90° Twist, 1 Inch 220 GHz to 325 GHz,

Specifications	
Frequency Range	220 GHz to 325 GHz
• VSWR	1.04:1
Impedence	50 Ohms
• Length	1 inch
• RF Ports	WR-3 Waveguide with UG-387/U-M Flange
Environmental Da	ata
Temperature Range	220°C Max
Material	
• Waveguide	Silver
• Flange	Round UG-387/U-M, Brass
• Finish	Gold Plated per MIL-DTL-45204

HWTW03-1-ER | 220 GHz to 325 GHz | Outline Drawing

