HWTW42-1-ES





The HASCO WR-42 Millimeter Waveguide 90° Twist **HWTW42-1-ES** operates from 18 GHz to 26.5 GHz. This WR-42, K-Band waveguide 90° twist is constructed with a Square UG-595/U Flange.

HASCO rectangular waveguides are manufactured from brass, OFHC copper, aluminum or coin silver. Waveguides have significant advantages over coaxial transmission in power handling, insertion loss and signal integrity (leakage and electromagnetic interference - EMI).

HASCO offers a series of millimeter waveguide straight sections, E-Bends, H-Bends and 90° Twists. Anticocking flanges available if required. All are available in standard and custom lengths covering the waveguide sizes WR-3, WR-4, WR-5, WR-6, WR-8, WR-10, WR-12, WR-15, WR-19, WR-22, WR-28, WR-34 and WR-42. Square waveguide flanges are available in WR-22, WR-28, WR-34 and WR-42. Please contact HASCO for custom options.

WR-42 Millimeter Waveguide 90° Twist, 1 Inch 18 GHz to 26.5 GHz, K-Band

Specifications

• Frequency Range 18 GHz to 26.5 GHz

• VSWR 1.02:1

Impedence 50 Ohms

• Length 1 inch

• RF Ports WR-42 Waveguide with UG-595/U Flange

Environmental Data


• Temperature Range 220°C Max

Material


• Waveguide OFHC Copper


• Flange Square UG-595/U, Brass

• Finish Gold Plated per MIL-DTL-45204



THIS DRAWING IS A CONTROLLED DOCUMENT





Part Number	WG Size	DIM A	DIM B
HWTW42-X-ES	WR-42	0.420	0.170
HWTW34-X-ES	WR-34	0.340	0.170
HWTW28-X-ES	WR-28	0.280	0.140

LTR	DESCRIPTION	DATE	APPR.	CREATED BY: JMS	CHECKED BY: TAC	
-	RELEASE	08/19	TAC	APPROVED BY: TAC		
				=== =	SPECIFICATIONS ARE THE	
				PROPERTY OF HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN		
				WHOLE OR IN PART - AS THE BASIS FOR THE MAN UFACTURE OR SALE OF OTHER ITEMS WITHOUT		
				THE EXPRESS, WRITTEN PERMISS COMPONENTS.	PERMISSION OF HASCO	



5214 Bonsai Street • Moorpark, CA 93021 (888) 498-3242 • sales@hasco-inc.com www.hasco-inc.com

-	MATERIALS: SEE DATA SHEET	CAGE CODE: 0T8L4	SCALE: N/A	SIZE:
)		PART NO./DRAWING NO.	REV:	
	FINISHES: SEE DATA SHEET	HWTW ²	12-1-ES	-

Product specifications subject to change without notification.